



INSTALLATION NOTES

1. CATCHBASIN IS TO BE INSTALLED AT BASE COURSE ASPHALT LEVEL. TEMPORARY ASPHALT CURB IS TO BE FORMED BETWEEN CURB EXPANSION JOINTS.
2. CATCHBASIN IS TO BE RAISED TO FINAL GUTTER LEVEL PRIOR TO PLACEMENT OF TOP COURSE OF ASPHALT AS PER OPSD 704.010. ASPHALT CURB IS TO BE REPLACED WITH PERMANENT CONCRETE CURB.

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. ALL CURBS AND GUTTERS TO BE INSTALLED PER OPSD.MUNI 353.
3. CONCRETE CURB AND GUTTER SHALL BE PER OPSD 600.040 OR OPSD 600.070, AS PER DESIGN.
4. JOINTS BETWEEN CURBS AND GUTTERS AND ADJACENT CATCHBASINS SHALL BE FORMED WITH 12mm THICK PANELS OF JOINT FILLER.
5. COMPRESSIVE STRENGTH OF THE CONCRETE CURB SHALL BE AT LEAST 32MPa AT 28 DAYS.

CATCH BASIN CURB DETAIL

REVISIONS

NO.	COMMENTS	BY	DATE	APPROVED BY	DATE APPROVED

CITY OF KAWARTHA LAKES  
ENGINEERING AND CORPORATE  
ASSETS

322 KENT ST. W, Box 9000, LINDSAY ON. K9V 4T7, (705) 324-9411

DRAWN BY: AK CHECKED BY: DATE: 2025/11/06

APPROVED BY: DATE:



CONTRACT NO:  
SCALE: 1:25  
PAGE 1 OF 1  
DRAWING NO.  
CKL - 409